

TWO YEARS *plus* a LIFETIME

LIFETIME WARRANTY ON MATERIALS: The concrete coating materials, used as described herein, applied by ARIZONA CREATIVE SURFACES, are guaranteed for LIFE to maintain its bond to the substrate it is applied to, under normal use.

TWO YEAR LABOR WARRANTY: If within 2 (TWO) YEARS from the date of installation, the CENTURYSTONE CONCRETE COATINGS, as applied by ARIZONA CREATIVE SURFACES, loses its bond due to defective materials or workmanship, it will be repaired at no charge, with the exception of the following exclusions:

- 1) There are some existing concrete slabs where moisture can cause a chemical reaction in the concrete that could result in blistering of the concrete coating. **THIS IS A REFLECTION ON THE QUALITY OF THE CONCRETE, NOT ON THE QUALITY OF THE COATINGS.** There are numerous causes of this condition (including **ALKALI SILICA REACTIVITY**) that originates at the time the concrete slab was originally poured. The repair of damage as a result of these conditions is not included in the warranty.
- 2) There is no guarantee that **CRACKS** will not occur in the coating due to movement of the concrete or deck surfaces on which the coating is applied, and the repair of such is **NOT** included in the warranty. It is presumed the substrate or surface on which the CENTURYSTONE CONCRETE COATINGS are applied is stable with adequate foundation and support.
- 3) **Caulking** or Joint sealant materials are guaranteed for a maximum of ONE YEAR.

If normal use results in excessive wear to the surface, the CENTURYSTONE CONCRETE COATINGS may require resealing in high traffic areas at intervals of 2 years (+/-) to maintain a higher level of sheen. This additional cost is not included in contract and is not considered warranty work.

Liability is limited to the value of the labor and materials used to repair damage defined by this warranty. After 2 (two) years from the date of installation labor will be charged @ the rate of **\$35.00/man/hour**.

INSTRUCTIONS AND CARE: CENTURYSTONE CONCRETE COATINGS have endured rigorous testing in both commercial and industrial applications. We are confident these systems will prove to be extremely durable and long lasting. However, these coatings are **NOT** indestructible. Extra care should be exercised for at least seven (7) days after installation.